



DCT FLUID

DESCRIPTION

DUAL CLUTCH TRANSMISSION (DCT) FLUID is a fully synthetic, multipurpose DCT FLUID formulated with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance.

DCT FLUID meets and exceeds current original equipment manufacturers specifications for dual clutch transmission fluids, including some of the latest OEM specifications as specified by VW, Audi, Seat, Skoda, Ford, Chrysler, Volvo, Mitsubishi, and others.

FEATURES AND ADVANTAGES

- Lubricates clutches, gears, shafts, bearings and synchronizers
- Superior heat dissipation
- Protection of transmission against wear and corrosion
- Outstanding friction and anti-shudder durability
- Extensively field tested

PERFORMANCE SPECIFICATIONS

DUAL CLUTCH TRANSMISSION (DCT) FLUID meets the requirements of transmission manufacturers where the following DCT types are specified:

OEM	Vehicle Model	Transmissions	Specifications
Audi	A3, TT	DQ250, DQ500	VW TL 052 182
Audi	A4, A5, A6, A7, Q5	DL501	VW TL 052 529
BMW (Getrag)	1, 3, 5, 6 series, Z4, X1	7DCI600, DCI700	83 22 2 148 578 83 22 2 148 579 83 22 0 440 214 83 22 2 147 477
Citroen	DS5, C5, C4, C-Crosser	6DCT451	Peugeot/Citroen 9734.S2
Ford/Getrag	Fiesta, Focus, Mondeo, B-Max, C-Max, S-Max, Galaxy, Transit	6DCT450, 6DCT451, 7DCT300	Ford M2C936A
Mercedes-Benz	A-Class, B-Class	F-DCT350, F-DCT500	MB 236.21 (001 989 85 03)
Mitsubishi	Outlander	6DCT470	MZ320065 Dia-Queen SSTF-I
Nissan	Qashqai	6DCT451	Ford M2C936A
Peugeot	4007, 5008	6DCT451	Peugeot/Citroen 9734.S2
Porsche (ZF)	Boxster, Cayman, 911, Panamera	ZF 7DT45HL, 7DT45HLA, 7DT45FL, 7DFL, 7DT70HLA, 7DT75, 7DT75A	Porsche Oil No. 999.917.080.00
Seat	Ibiza, Toledo, Leon, Altea	DQ250, DQ500	VW TL 052 182
Skoda	Fabia, Yeti, Octavia, Superb	DQ250, DQ500	VW TL 052 182
Volkswagen	Golf, Golf Plus, Eos, Scirocco, Caddy, Touran, Tiguan, Passat, Transporter, Sharan	DQ250, DQ500	VW TL 052 182
Volvo	C30, S40, S60, V40, V50, V60, V70 S80, XC30, XC60	6DCT450	1161838 1161839

Note: Not recommended wherever ATF or CVT fluids or Type F or Power Steering Fluids are specified Suitable for use wherever other DCT fluids are in use.

TYPICAL SPECS

Specific Gravity @ 15.6°C	0.856
Lbs/Gal @ 15.6°C	7.21
Viscosity @ 100°C, cST	6.97
Flash Point, °C, COC	194
Pour Point, °C	-54
Color, D-1500	Bright and Clear
Base Number (mg KOH/g)	4.8
Elastomer Compatibility (NBR / FKM / ACM / AEM)	Passes
Product Number:	13051
Product Carton Size	12x1 L

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA 94401, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com