



**TOP 1 OIL PRODUCTS COMPANY**

**Product Data Sheet**

Revised: Mar. 2015  
Code: 31001, 31003, 31004, 31006

# MULTI-PURPOSE (MP) GEAR OIL

## DESCRIPTION

**MULTI-PURPOSE (MP) GEAR OILS** are thermally stable, extreme pressure, multi-purpose gear lubricants formulated to withstand the most severe conditions including extreme temperatures and high load conditions. These long-life gear oils exceed API service classification GL-5/MT-1. MP GEAR OILS are manufactured from the highest quality base oils fortified with VI improvers, rust inhibitors, foam suppressants, anti-wear, and extreme pressure additives and pour point depressants. These multi-viscosity grades may be used over wide temperature ranges.

## FEATURES AND ADVANTAGES

- Exceeds API GL-5
- SAE J2360
- Mack Specification GO-J
- Exceptional thermal and oxidation stability
- All-weather protection
- Long lubricant life
- Protects hypoid gears from wear and scuffing
- Multi-viscosity provides year round use
- Compatible with other automotive gear oils

## TYPICAL SPECS

GRADE, SAE	90	140	80W-90	85W-140
Gravity, °API	25.1	23.8	26.0	24.5
Flash Point, °C	216	227	213	221
Pour Point, °C	-15	-18	-32	-15
Viscosity @ 40°C, cSt	229	523	172	347
Viscosity @ 100°C, cSt	19.2	31.7	16.3	25.5
Viscosity Index	95	90	98	96
Color, D1500	5.0	7.0	5.5	7.0
Brookfield, cPs (-26°C)			90,000	
Brookfield, cPs (-12°C)				85,000
<b>Product Number:</b>				
1x18.95 L (5 Gal)	10325	10335	10355	10345
1x200 L (53 Gal)	10327	10337	10357	10347
1x208 L (55 Gal)			10357-55	10347-55

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

100 N. El Camino Real, San Mateo, CA, 94401, Tel: 650.347.3691 Fax: 650.340.8739 www.top1oil.com