Revised: Aug 2011

## TOP 1 EVOLUTION (HDMO)

## **DESCRIPTION**

**TOP 1 EVOLUTION (HDMO)** CJ - 4 / SM is a blend of premium synthetic base oils and selected additives, designed to give excellent performance in all emission compliant engines using ultra low sulfur diesel fuel (ULSD). This engine oil contains an effective additive system, which is DPF compatible and keeps the EGR engines highly clean. It can be used for all new and old engines using ULSD fuel and safe for usage with most of the After Treatment Devices (ATD).

## FEATURES AND ADVANTAGES

- •Recommended for all EPA 2007 compliant engines using DPF after treatment device and ULSD fuel that specify CJ-4 / Cl-4 plus / Cl-4 / CH-4 / CG-4 / CF-4 /CF / SM, & European and OEM claims.
- It also meets ACEA E7, MB 228.3, Volvo VDS- 4, Cummins CES 20081, Mack EO-O premium plus'07, Caterpillar ECF 3 & ECF1, DDC PGOS 93 K 218, MAN 3275, MTU Type II specification
- Meets and exceeds tomorrows EPA compliant engine requirements.
- •High TBN with low SAPS.
- •DPF & all ATD compatible.
- ·Backward compatible with all Old and New engines using ultra low sulfur diesel fuel.

## TYPICAL SPECS

| <b>GRADE, SAE</b> API Gravity | ASTM TEST<br>D-287 | <b>5W40</b> 34.0 |
|-------------------------------|--------------------|------------------|
| Flash Point, °F               | D-92               | 440              |
| Pour Point, °C                | D-97               | -30              |
| Viscosity:                    |                    |                  |
| cST @ 100°C                   | D-445              | 14.5             |
| CCS @ -25°C                   | D-5293             | 6000             |
| Viscosity Index               | D-2270             | 145              |
| Appearance                    | Visual             |                  |
| Color                         | D-1500             | 3.0              |
| Calcium, wt%                  |                    |                  |
| Magnesium, wt%                |                    |                  |
| Phosphorus, wt%               |                    |                  |
| Zinc, wt%                     |                    |                  |
| Sulfated Ash, wt%             | D-874              | 1.0              |
| TBN                           | D-2896             | 10.5             |
| Product Number:               |                    |                  |
| 12x1 Liter                    |                    | 18771            |
| 4x5 Liter                     |                    | 18774            |
| 1x18.95 Liter                 |                    | 18775            |
| 1x200 Liter                   |                    | 18777            |
|                               |                    |                  |